



Product Bulletin

Product Name	CEDEPAL® TD-403 MKLD
Chemical Structure	$C_{13}H_{27}(OCH_2CH_2)_nOSO_3Na$
Chemical Description	Sodium Tridecyl Ether Sulfate
CAS Registry Number	25446-78-0
INCI Name	Sodium Trideceth Sulfate
Applications	CEDEPAL TD-403 MKLD is a mild branched chain alkyl ether sulfate. It is used in personal care products including shampoos, hand soaps and bath products. It has excellent wetting and foaming properties. It is also used for mild cleansing and baby products and it is used as an emulsifying agent.
Typical Properties	<p>Appearance at 25°C Clear, light yellow liquid</p> <p>pH, 10% aqueous 5.8</p> <p>Actives, % (EW 434) 30</p> <p>Color, Gardner 4 max.</p> <p>Viscosity at 0°C, cps 2,060</p> <p>Viscosity at 25°C, cps 700</p> <p>Viscosity at 60°C, cps 160</p> <p>Flash Point, PMCC, °C (°F) >94 (>201)</p> <p>Density, g/ml (lbs/U.S. gal) 1.03 (8.6)</p> <p>RVOC, U.S. EPA, % 0</p> <p>Preservative Methylchloroisothiazolinone/Methylisothiazolinone</p>
Environmental Effects	Product is biodegradable. A detailed biodegradability statement is available upon request.
Storage & Handling	<p>Normal safety precautions (e.g., gloves and safety goggles) should be employed when handling CEDEPAL TD-403 MKLD. Contact with eyes, nose or prolonged contact with skin should be avoided. Wash thoroughly after handling CEDEPAL TD-403 MKLD. See SDS for more information.</p> <p><u>Standard Packaging:</u> CEDEPAL TD-403 MKLD is available in drums, totes, and bulk quantities.</p> <p><u>Non-Bulk Storage Recommendations:</u> CEDEPAL TD-403 MKLD should be stored in closed containers and kept in a cool, dry place away from incompatible materials (see Section 10 of the SDS). If material is frozen it should be heated gently and stirred to ensure it is homogeneous prior to use. Polyethylene drums are recommended for storage of CEDEPAL TD-403 MKLD.</p> <p><u>Bulk Storage Recommendations:</u> CEDEPAL TD-403 MKLD should be stored in 316 stainless steel or fiberglass with a corrosion liner. Mild agitation is recommended while storing to maintain homogeneity. Material should be stored between 73-104°F (23-40°C). An internal hairpin coil of 316 stainless steel with low pressure steam (under 50 psig) should be used if heating is required. Pumps, pipes and transfer lines should be 316 stainless steel.</p>

CEDEPAL® is a registered trademark of Stepan Company.



Due to the sensitivity of the Methylchloroisothiazolinone/Methylisothiazolinone preservative, the storage temperature should not exceed 110°F (43°C) for any extended period of time. Degradation of the preservative is accelerated by temperature > 104°F (>40°C).

Workplace Exposure

Occupational exposure can occur primarily through skin contact or via inhalation of vapors and mists. Engineering controls, personal protective equipment, and other workplace safety practices should be used to control these exposures. See SDS for more information.

Clearances

The international inventories (country clearances) of CEDEPAL TD-403 MKLD can be found in Section 15 of the Safety Data Sheet (SDS). It is the responsibility of the formulator to review the chemical control regulations for each country where the end-product is intended to be sold or used. If you have any further questions regarding inventories, please contact North America Technical Service at techserv@stepan.com.

Product Stewardship

This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

Additional Safety Information

A Safety Data Sheet (SDS) is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the information provided herein, including in respect of its accuracy, completeness, adequacy, furnishing, or use, or reliance upon such information. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

Stepan 
Corporate Headquarters
Northfield, Illinois 60093, U.S.A.
Phone: 847-446-7500
Fax: 874-501-2100
Website: www.stepan.com

For Technical Service Call:
 Stepan North America **+1-800-745-7837**
 Stepan Mexico **+55-11-5089-2208**
 Stepan Quimica **+55-11-5089-2200**
 Stepan Colombia **+571-636-2808**
 Stepan Europe **+33-476-505-160**
 Stepan Asia **+656-879-9855**
 Stepan Philippines **+656-879-9855**

For Customer Service Call:
 Stepan North America **+1-800-457-7673**
 Stepan Mexico **+52-555-533-1967**
 Stepan Quimica **+55-11-5089-2200**
 Stepan Colombia **+57-6-8993125**
 Stepan UK **+44-161-338-5511**
 Stepan France **+33-476-50-51-00**
 Stepan Philippines **+63-2-842-7951**