

Name INDUSTRIAL MASTIC REMOVER

No. 1206

Description This formulation removes mastic from hard flooring before, during, and after its installation.

Formulation INGREDIENTS: % by Weight Functionality

> BIO-SOFT® N1-7 5.0 Emulsifier STEPOSOL® MET-10U 45.0 Surfactant/Solvent

d-Limonene (Florida Chemical) 50.0 Solvent

Total 100.0

Procedure

1. Charge d-Limonene in mixing vessel.

2. With good agitation, blend in BIO-SOFT® N1-7.

3. Once clear, add STEPOSOL® MET-10U.

4. Mix until homogenous.

Physical **Properties**  Appearance at 25°C Clear liquid pH, as is 10.5 Viscosity at 25°C, cps Water thin 50

VOC (calculated), %

Storage/ Stability

Freeze/thaw, 3 cycles **Pass** 4 weeks at 50°C **Pass** 4 weeks at 4ºC **Pass** 4 weeks at 25°C **Pass** 

Instructions for Use

Apply to surface. Allow solution to penetrate for a few minutes. Then wipe with a clean cloth.

External Comment

Marketing Notes: Please refer to the Safety Data Sheet for global regulatory information. It is the responsibility of the end user to review the chemical control regulations for each country. BIO-SOFT® N1-7 is an approved ingredient on www.cleangredients.org. For further information. visit www.cleangredients.org. BCI = 68. Total BCI (Biorenewable Carbon Index) was calculated only for the Stepan surfactants used in this formulation. For further information on Stepan's BCI, visit www.stepan.com. This formulation does not meet the California Air Resource Board (CARB) VOC regulation for Consumer Products. "Consumer" is defined by CARB as any person who seeks, purchases, or acquires any consumer product for personal, family, household, or institutional use. For U.S. formulators, STEPOSOL® MET-10U is a low vapor pressure VOC (LVP-VOC), therefore its contribution to the VOC calculation is zero. STEPOSOL® MET-10U does not contribute to the VOC calculation because of its high boiling point and low vapor pressure. Before using on plastic, hard or painted surfaces, spot test on an inconspicuous area first. Patent Pending.

Registered Trademarks of Stepan

**BIO-SOFT®** STEPOSOL®

## Company

For Additional Assistance For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe).

For ordering assistance, call our Account Service Department at 1-800-457-7673.

Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

Stepan <sup>5</sup>

Stepan Company Northfield, Illinois 60093 Telephone (847) 446-7500

Revision Date: Publication Date: 03/18/2014 © 2014, Stepan Company. All rights reserved.